



* Shown with optional strike zones, front downlighting, and network display.

Features and Benefits

- **Stylish kiosk with curved front and canopy** creates appealing ATM environment
- **Replaceable front ATM panel with recessed ATM opening** protects your ATM
- **Recessed based on front body panel** allows for vehicle bumper clearance
- **Patented Straight Line Suspension (SLS) System** distributes the ATM weight throughout the kiosk frame
- **Seamless, composite roof with internal drainage system** prevents leakage and eliminates unsightly streaking
- Includes **backlit front sign, envelope dispenser, and climate control system**
- Meets **seismic zone 4 requirements, wind shear 120 mph**, and is **UL-listed**
- Additional options include: **backlit side and rear signs, front and rear downlighting, strike zones**, and more...

*rear downlighting and rear backlit signs can not be ordered together

Materials

Fiberglass composite shell
Fiberglass composite roof
Interior steel structure

ATM Compatibility

Diebold
Opteva 740, 1073i, 1073ix, 1077ix

NCR
5688, 5887, 5888, 6634

Wincor Nixdorf
ProCash 2250, ProCash 2250xe

Nautilus Hyosung
Monimax 5100T, 7000D, 7600D

Tranax
MBS5000DR

Patent: US 6,457,277 B1

